

DESCRIPTION

Exsan Radiator Leak Sealing formula is a finely powdered organic compound. It is free from silicates, metallic powders, starch, sugar & any other material that produces detrimental or harmful effect to the cooling system components. It seals leak in Copper, Aluminium, Metal and Plastic radiators and inhibits rust and corrosion. It also lubricates water pump seal; helps neutralize pH imbalance and controls electrolysis. It prevents scale formation in the cooling system.

APPLICATION

Exsan Radiator Stop Leak (Powder) when put into the radiator disperses fully to seal and protect the cooling system against seepages & minor leaks. The product can be used in advance or as a precautionary measure to avoid minor leak or seepage.

PROPERTIES

Sl. No.	Properties	Unit	Specification
1	Appearance	--	Powder
2	Color	–	Brown
3	Hardness	Shore A	75 - 90
4	Corrosion test	--	No corrosion
5	Foaming Test	–	No foaming
6	pH(1% solution)	–	6.0 - 8.0

DOSAGE

- Add 50 gms into the radiator for the vehicles of 600 CC to 1500 CC.
- Add 75 gms – 100 gms into the radiator for the vehicles above 1500 CC.

DIRECTIONS FOR USE

- Add pellets into the radiator coolant at the above-recommended dosage.
- Run the engine for 3 minutes in neutral position.

CAUTION : Avoid keeping load on the pack. Avoid contact with eyes. Avoid inhalation and opening radiator cap when the engine is hot.

SHELF LIFE : Nine months from the month of manufacture.

STORAGE : Store in cool dry place away from heat source and direct sunlight.

PACKING : 50 gms / 24 nos in a carton.

The information contained herein is based on the present state of our knowledge. However, testing under actual condition by the user is recommended