



DESCRIPTION

It is a NLGI grade grease processed from refined petroleum base stocks and thickened with calcium soap of blended fats / fatty acids of natural origin.

BENEFITS

- Grease has good surface adhesion and thus resistant to wear, dust, dirt, corrosion and oxidation. It provides smoother lubrication.
- It is also operating at high temperatures ranging from -20° c to 120°c.
- Chassis grease is water repellent.

PROPERTIES

S.No	Perticulars	Specification
1	Colour	Green and Yellow
2	Soap base	Calcium
3	Appearance	Smooth Stringy
4	Worked penetration @ 25°C	290 - 310
5	Drop Point °C min	94
6	Copper Corrosion 4 Ball weld Load	- Ve
7	Service Temperature	- 20°C to 120°C

Recommended for

General & non-critical lubrication in automotive lubricants, farm machinery, trucks, buses and cars.

Packing Information

Package - 500 gms / 1 Kg / 2 Kg / 3 Kg / 5 Kg / 15 Kg / 25 Kg / 50 Kg / 180 Kg

Storage - Store in Room Temperature. Keep away from Direct UV.

(The Information given herein correspond to the practical experience and to the best of our knowledge. No warranty is expressed or implied regarding accuracy of said data. Owing to differences in local conditions, it is the users responsibility to determine the suitability of the products described herein for their own use. We dis-claim any liability with respect to the use of any material supplied by us).