



DESCRIPTION

Lithium soap base containing graphite Powder. The Behavior of Graphite powder under friction compares favorably by its adsorption properties regards to water & other vapors

BENEFITS

- Grease has good shear stability and surface adhesion.
- It is an Anti seize compound on threads of steel nuts and bolts
- It is also operating at high temperatures ranging from - 20° c to 500°c.

PROPERTIES

S.No	Perticulars	Specification
1	Colour	Grayish Back
2	Soap base	Lithium & Graphite
3	Appearance	Buttery
4	Worked penetration @ 25°C	265 - 295
5	Drop Point °C min	185
6	Copper Corrosion 4 Ball weld Load	1A
7	Service Temperature	- 20°C to 500°C

RECOMMENDED FOR

Universal joints, steel gears, wire rope lubricant, springs & leaf springs in automobiles and railways. It is also used for exposed parts of farm machinery.

PACKING INFORMATION

Package - 500 gms / 1 Kg / 2 Kg / 3 Kg / 5 Kg / 15 Kg / 25 Kg / 50 Kg / 180 Kg

Storage - Store in Room Temperature. Keep away from Direct UV.

(The Information given herein correspond to the practical experience and to the best of our knowledge.No warranty is expressed or implied regarding accuracy of said data. Owing to differences in local conditions, it is the users responsibility to determine the suitability of the products described herein for their own use. We dis-claim any liability with respect to the use of any material supplied by us).