



DESCRIPTION

It High temperature Lithium Complex grease processed for lubricating upto 160° c under normal to heavy loads. The complex additives soap and the additives incorporated in this grease enables to retain its structure at hi temperature and under heavy loads

BENEFITS

- Grease has good shear stability and surface adhesion and thereby reducing leakage tendency and extension of re-lubrication intervals. It is also available in NLGI 2 and 3 consistency.
- It is also operating at high temperatures ranging from -20° c to 160°c.
- Lithoplex grease is water repellent and is not compatible with conventional and Soda base grease.

PROPERTIES

S.No	Perticulars	Specification
1	Colour	Yellow / Red / Blue / Green
2	Soap base	Lithium Complex
3	Appearance	Smooth buttery
4	Worked penetration @ 25°C	265 - 295
5	Drop Point °C min	250
6	Copper Corrosion 4 Ball weld Load	- Ve 315
7	Service Temperature	- 20°C to 160°C

RECOMMENDED FOR

Lubrication of all types bearings under higher than ambient temperature and heavy loads. Electric, Ceramic & metallurgical industry.

PACKING INFORMATION

Package - 500 gms / 1 Kg / 2 Kg / 3 Kg / 5 Kg / 15 Kg / 25 Kg / 50 Kg / 180 Kg

Storage - Store in Room Temperature. Keep away from Direct UV.

(The Information given herein correspond to the practical experience and to the best of our knowledge. No warranty is expressed or implied regarding accuracy of said data. Owing to differences in local conditions, it is the users responsibility to determine the suitability of the products described herein for their own use. We dis-claim any liability with respect to the use of any material supplied by us).