



DESCRIPTION

Processed from refined petroleum base stocks and thickened with selected & blended fats / fatty acids of natural origin. It has good shear stability and surface adhesion and hence prevents wear, rust and corrosion. It is not resistant to water & non compatible with other greases.

BENEFITS

- Grease has good shear stability, surface adhesion and thus resistant to wear, Dust, dirt, corrosion and oxidation.
- Grease is suitable for automotive equipment, contractor equipment, farm, truck and bus operation. It is also operating at high temperatures ranging from -20° c to 120°c.
- Grease is not water resistant and not compatible with other greases.

PROPERTIES

S.No	Perticulars	Specification
1	Colour	Dark Greenish black
2	Soap base	Sodium
3	Appearance	Medium Fiber
4	Worked penetration @ 25°C	220 - 250
5	Drop Point °C min	180
6	Copper Corrosion 4 Ball weld Load	- Ve
7	Service Temperature	- 20°C to 120°C

RECOMMENDED FOR

Ball bearings, wheel and axle bearing open and driving gears.

PACKING INFORMATION

Package - 500 gms / 1 Kg / 2 Kg / 3 Kg / 5 Kg / 15 Kg / 25 Kg / 50 Kg / 180 Kg

Storage Store in Room Temperature. Keep away from Direct UV.

(The Information given herein correspond to the practical experience and to the best of our knowledge. No warranty is expressed or implied regarding accuracy of said data. Owing to differences in local conditions, it is the users responsibility to determine the suitability of the products described herein for their own use. We dis-claim any liability with respect to the use of any material supplied by us).